




PROJECT	DATE
TYPE	QTY

# StoneGlow™ RGBW

**LED Light Sheet** 

Cut the 12" x 24" (2 sq ft) sheet to size at the job site to achieve a perfect fit for your application.

Included clear rubber spacers help lift and support material like "Onyx" a half-inch off the light sheet for a leveled and diffused light effect.



Set your mood and illuminate your space with StoneGlow™ RGBW LED Sheets. Perfect for counter tops and architectural fixtures.

**Create Stunning Back-lit Designs:** Ideal for back-lighting translucent material like "Onyx" for counter tops, wall art, display cases, and custom lighting fixtures.

**Easy to Install:** With 3M peel and stick backing installation is quick and versatile.

**Even Glow Lighting Effects:** Included spacers, lift and support the material you are backlighting by half an inch, creating even and diffused effects.

### **FEATURES**

- 4-in-1 RGB + 4500K Warm White
- · Ideal for back lighting translucent materials
- Up to 1000Lm output performance per sheet
- Available in 12"H x 24"W ( 2 sq ft ) sheet size
- · Field cuttable on-site for an accurate fit
- 3M peel and stick backing for quick installation
- Built-in terminal ports make it easy to run power from any side.
- Spacers included, to lift and support material 1/2" to create even lighting.





StoneGlow™ R	RGBW LED SHEET SPECS
VOLTAGE	24V DC
WATTAGE	20W per sheet
LUMENS	Up to 1000Lm per sheet
ССТ	RGB + 4500K
CRI	90+
MAX RUN	96W (4-1/2 Sheets Total) Per Wire
IP RATING	IP54
DIMMING	5 - 100%
DIMENSIONS	12" (304.8mm) W x 24" (609.6mm) H
<b>BEAM ANGLE</b>	120°
<b>OPERATING TEMP</b>	-20°C (4°F) to 45°C (113°F)
CERTIFICATIONS	cULus Listed - Maintains UL listing when cut
RATED LIFE	50,000 Hours - 25 Years @5/Night at full brightness - Afterwards, some dimming will occur.







PROJECT	DATE
TYPE	QTY


### StoneGlow™ LED SHEET / RGBW

### StoneGlow™ LED SHEET / RGBW QUICK DIMENSIONS



## Cut into any shape you need





Sheet to Sheet Jumper Linking - Recommended Wire Gauge: 22AWG (Standard Core)





PROJECT	DATE
TYPE	QTY

## StoneGlow™ LED SHEET / RGBW

StonoGlowTM	IED	CHEET	/ PCRW	OBDEDING	INFORMATION
Stollediow		SHILLI	/ IZGDVV	CHILITATION	

ITEM NUMBER	VOLTAGE	CCT	LENGTH	LUMENS	WATTAGE	IP RATING	CRI	MAX RUN
II -SG-RGBW-12x2	24 V DC	RGBW	12" x 24" ( 2 sq ft)	1000Lm	20W	IP54	90+	96W per lead wire

StoneGlow™ LED SHEET / RGBW CONTROLLERS				
ITEM NUMBER	DESCRIPTION			
IL-SG-CTL-APP-WALL-CTR	Star Control APP plus Wall Controller			
IL-SG-CTL-RGBW-DMX	DMX Controller			
IL-SG-CTL-RGBW-RS232-SERIAL	RS232 Serial Controller			
IL-SG-CTL-RGBW-WIRELESS-ON-OFF	Simple On/Off			
IL-SG-CTL-RGBW-REMOTE	Remote			

### StoneGlow™ LED SHEET / RGBW POWER SUPPLIES

ITEM NUMBER	DESCRIPTION	
IL-SG-PS-20W	20W Power Supply	
IL-SG-PS-60W	60W Power Supply	
IL-SG-PS-96W	96W Class II Power Supply	
IL-SG-PS-150W	150W Class II Power Supply	
IL-SG-PS-320W	320W Class II Power Supply	

#### StoneGlow™ LED SHEET / RGBW ACCESSORIES

ITEM NUMBER	DESCRIPTION
IL-SG-J2	2" Jumper
IL-SG-J8	8" Jumper
IL-LW-8	8" Lead Wire
IL-SG-SP-25	Spacers, bag of 24
IL-SG-CON	Connectors

#### **ORDERING**

MODEL	CONTROLLER	POWER SUPPLY	ACCESSORIES
IL-SG-RGBW	]	-	_
StoneGlow™ RGBW StoneGlow™ CWWW StoneGlow™ WH	1 = Star Control APP-WALL-CTR 2 = DMX Controller 3 = RS232 Serial 4 = Simple On/Off 5 = REMOTE	1 = 20W PS 2 = 60W PS 3 = 96W Class II PS 4 = 150W Class II PS 5 = 320W Class II PS	1 = 2" Jumper 2 = 8' Jumper 3 = 8" Lead Wire 4 = Spacers - 24 Qty 5 = Connectors