



***Epix Acoustic Diamond Series Wall Panels** are design forward structures created to diffuse and clarify sound in your entertainment environments. Innovative design & LED back lighting effects are the designers choice for incorporating form and function.*



SOUND PROOF WITH STYLE

Acoustic panels not only absorb and diffuse sound in your entertainment and relaxation environments, but can add high end design as well



DESIGN, TEXTURE, ACOUSTICS

Ideal in home theaters, hospitality and wellness applications. EpiXsky acoustic wall panels come in 3 standard designs and fabrics with **back-lit** controllable color changing or single color LED lights. Custom designs and fabric colors **available**.



FASTER SMOOTHER COMMUNICATION

- 1 inch high quality fabric acoustical panels
- UL fire rated materials
- Lighting can be controlled independently or via home automation RS232 serial command.
- Wifi option for control flexibility.
- 5 Year Limited Warranty



A Division of Impact Lighting Inc.



2814 Silver Star Rd., Orlando, Florida 32808 • Ph. 1-800-507-5714 • Email: sales@epixsky.com

epixsky.com

SPECIFICATION ACOUSTIC PANELS

PROJECT	DATE
TYPE	QTY



FABRIC COLOR OPTIONS FOR ACOUSTIC WALL PANEL ART

LIME	CHARTREUSE	CARDINAL	SKY
TEAL	FIR	YELLOW	SAPPHIRE
ORANGE	BLUE PAPIER	WHEAT	★ EGGSHELL
WEDGEWOOD	BALTIC	CRYSTAL BLUE	★ WHITE
GREY MIX	★ MEDIUM GREY	QUARTZ	AQUAMARINE
OPAL	CHERRY NEUTRAL	BLUE NEUTRAL	GREEN NEUTRAL
VANILLA NEUTRAL	APRICOT NEUTRAL	LAVENDAR NEUTRAL	SILVER NEUTRAL
★ BLACK	CLARET ACCENT	COBALT	CINNABAR
PUMICE	BUFF	BLUE SPRUCE	EUCALYPTUS
ULTRAMARINE	STEEL GREY	PEARL	★ BAYBERRY
SILVER PAPIER	★ BLUE PLUM	DEEP BURGUNDY	VERTE PAPIER
STRAW	BONE	DUNE	CEMENT MIX
TERRA	LIGHT MOSS	LEAF	STREAM
DESERT SAND	EARTH	CHOCOLATE	COIN
FLANNEL	MOLESKIN	SUNSHINE	IRIS
	RED	AMETHYST	

(* Standard Colors)

SPECIFICATIONS:

CONTENT:

65% pre-consumer recycled polyester
35% post-consumer recycled polyester

WEIGHT:

15.0 ± 1.0 oz./lin. yd.

WIDTH:

66" min. usable

REPEAT:

none

BACKING:

none

CLEANING CODE:

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

PERFORMANCE:

Breaking Strength (ASTM D5034

275 lbf min. warp and fill

Pilling Resistance (ASTM D3511)

Class 4 min.

Colorfastness to Light (AATCC 16.3 Option 3

Grade 4 min. at 40 hours

Colorfastness to Crocking (AATCC 8)

Grade 4 min. dry & Grade 3 min. wet

Flammability

**CA Technical Bulletin 117-2013 Section 1 ASTM E84
Class I or A**

NRC of anechoic termination **1.00**

NRC of fabric in front of anechoic termination **.85**



100% recycled and recyclable

Terratex is a registered trademark of Duvaltex



This pattern is included in the underwriters laboratory panel fabric recognition program. Additional testing of this U.L. recognized fabric is not required on approved panels from participating manufacturers.

ORDERING

MODEL	—	COLOR	—	COLOR 2
APF				
Acoustic Panel Fabric		Choose From Above		Choose From Above